



DEEP CYCLE
SERIES: 4000
MODEL: S-600

BATTERY ENGINEERING
WWW.ROLLSBATTERY.COM MADE IN CANADA

BATTERY TYPE: 6 VOLTS

DIMENSIONS:

LENGTH	318 MM	12 1/2 INCHES
WIDTH	181 MM	7 1/8 INCHES
HEIGHT	425 MM	16 3/4 INCHES

WEIGHTS:

WEIGHT DRY	44 KG	97 LBS.
WEIGHT WET	55 KG	122 LBS.

CONTAINER CONSTRUCTION:

CONTAINER: HIGH DENSITY POLYPROPYLENE
COVER: HIGH DENSITY POLYPROPYLENE

TERMINALS: FLAG TERMINAL
HANDLES: ROPE

PLATES:

POSITIVE PLATE DIMENSION:

HEIGHT	273 MM	10.750 INCHES
WIDTH	143 MM	5.625 INCHES
THICKNESS	4.32 MM	0.170 INCHES

CELLS: 3
PLATES/CELL: 19

NEGATIVE PLATE DIMENSION:

HEIGHT	273 MM	10.750 INCHES
WIDTH	143 MM	5.625 INCHES
THICKNESS	3.05 MM	0.120 INCHES

SEPARATOR THICKNESS: 2 MM 0.061 INCHES
INSULATION GLASS MAT: 1 MM 0.020 INCHES

CAPACITY:

CRANK AMPS:
COLD (CCA) 0°F / -17.8°C 1370
MARINE (MCA) 32°F / 0°C 1713

ELECTROLYTE RESERVE:
ABOVE PLATES 57 MM 2.25 INCHES
RESERVE CAPACITY:
RC @ 25A 979 MINUTES

20 HR RATE: 450

	HOUR RATE	SPECIFIC GRAVITY	CAP / AH	CURRENT / AMPS
CAPACITY @	100 HOUR RATE	1.280 SP. GR.	599	5.99
CAPACITY @	72 HOUR RATE	1.280 SP. GR.	567	7.88
CAPACITY @	50 HOUR RATE	1.280 SP. GR.	536	10.71
CAPACITY @	24 HOUR RATE	1.280 SP. GR.	464	19.3
CAPACITY @	20 HOUR RATE	1.280 SP. GR.	450	22.5
CAPACITY @	15 HOUR RATE	1.280 SP. GR.	423	28.2
CAPACITY @	12 HOUR RATE	1.280 SP. GR.	401	33.4
CAPACITY @	10 HOUR RATE	1.280 SP. GR.	383	38.3
CAPACITY @	8 HOUR RATE	1.280 SP. GR.	360	45.0
CAPACITY @	6 HOUR RATE	1.280 SP. GR.	333	55.5
CAPACITY @	5 HOUR RATE	1.280 SP. GR.	315	63
CAPACITY @	4 HOUR RATE	1.280 SP. GR.	293	73
CAPACITY @	3 HOUR RATE	1.280 SP. GR.	266	89
CAPACITY @	2 HOUR RATE	1.280 SP. GR.	230	115
CAPACITY @	1 HOUR RATE	1.280 SP. GR.	162	162



www.antusolar.cl
contacto@antusolar.cl



REV.2
 Apr-10
 S-600