



DEEP CYCLE
SERIES: 4000
MODEL: 6 EHG 31P

BATTERY ENGINEERING
WWW.ROLLSBATTERY.COM MADE IN CANADA

BATTERY TYPE: 6 VOLTS

DIMENSIONS:

LENGTH	527 MM	20 3/4 INCHES
WIDTH	203 MM	8 INCHES
HEIGHT	324 MM	12 3/4 INCHES

WEIGHTS:

WEIGHT DRY	47 KG	104 LBS.
WEIGHT WET	60 KG	133 LBS.

CONTAINER CONSTRUCTION:

CONTAINER: (INNER)	POLYPROPYLENE	TERMINALS:	FLAG WITH STAINLESS STEEL NUTS AND BOLTS
COVER: (INNER)	POLYPROPYLENE - HEAT SEALED TO INNER CONTAINER	HANDLES:	MOLDED
CONTAINER: (OUTER)	HIGH DENSITY POLYETHYLENE		
COVER: (OUTER)	HIGH DENSITY POLYETHYLENE SNAP FIT TO OUTER CONTAINER		

PLATES:

POSITIVE PLATE DIMENSION:

HEIGHT	162 MM	6.375 INCHES
WIDTH	143 MM	5.625 INCHES
THICKNESS	3.81 MM	0.150 INCHES

CELLS: 3
PLATES/CELL: 31

NEGATIVE PLATE DIMENSION:

HEIGHT	162 MM	6.375 INCHES
WIDTH	143 MM	5.625 INCHES
THICKNESS	2.49 MM	0.098 INCHES

SEPARATOR:
THICKNESS 2 MM 0.065 INCHES
INSULATION:
GLASS MAT 1 MM 0.020 INCHES

CAPACITY:

CRANK AMPS:		
COLD (CCA)	0°F / -17.8°C	1721
MARINE (MCA)	32°F / 0°C	2151

ELECTROLYTE RESERVE:
ABOVE PLATES 44 MM 1.75 INCHES
RESERVE CAPACITY:
RC @ 25A 934 MINUTES

20 HR RATE: 410

	HOUR RATE	SPECIFIC GRAVITY	CAP / AH	CURRENT / AMPS
CAPACITY @	100 HOUR RATE	1.280 SP. GR.	545	5.45
CAPACITY @	72 HOUR RATE	1.280 SP. GR.	517	7.18
CAPACITY @	50 HOUR RATE	1.280 SP. GR.	488	9.76
CAPACITY @	24 HOUR RATE	1.280 SP. GR.	422	17.6
CAPACITY @	20 HOUR RATE	1.280 SP. GR.	410	20.5
CAPACITY @	15 HOUR RATE	1.280 SP. GR.	385	25.7
CAPACITY @	12 HOUR RATE	1.280 SP. GR.	365	30.4
CAPACITY @	10 HOUR RATE	1.280 SP. GR.	349	34.9
CAPACITY @	8 HOUR RATE	1.280 SP. GR.	328	41.0
CAPACITY @	6 HOUR RATE	1.280 SP. GR.	303	50.6
CAPACITY @	5 HOUR RATE	1.280 SP. GR.	287	57
CAPACITY @	4 HOUR RATE	1.280 SP. GR.	267	67
CAPACITY @	3 HOUR RATE	1.280 SP. GR.	242	81
CAPACITY @	2 HOUR RATE	1.280 SP. GR.	209	105
CAPACITY @	1 HOUR RATE	1.280 SP. GR.	148	148