

Gama MBC



Modelo	MBC 12-06/1	MBC 12-15/1	MBC 24-03/1	MBC 24-08/1	MBC 24-32/1
Tensión de batería (Vdc)	12	12	24	24	24
Tensión de entrada (Vac)	100-260 (40 - 60 Hz)				
Tensión de carga (boost) (Vdc)	14.4	14.4	28.8	28.8	28.8
Tensión de carga (float) (Vdc)	13.8	13.8	27.6	27.6	27.2
Salida (A)	6	15	3	8	32
Refrigeración	Disipador de calor				
Salidas	1				
Rendimiento	> 85 %				
Temperatura de trabajo	-25 a 50°C				
Dimensiones LxaxA (mm)	155x80x36	195x100x47	155x80x36	195x100x46	158x245x47.5
Peso (kg)	0.9	1.8	0.9	1.8	3.8
Capacidad de batería recomendada (Ah)	18-60	45-150	9-30	24-80	20 >
Cambio a modo flotación (A)	0.2	0.8	0.2	0.4	3.5
Fusible secundario (A)	7.5	20	7.5	15	40
Cableado interno	•	•	•	•	•
Cableado externo	•	•	•	•	•
Garantía	2 años				



www.antisolar.cl
contacto@antisolar.cl

